



Certificate no.:
TAS00004VH

TYPE APPROVAL CERTIFICATE

This is to certify:
that the offshore container

with type designation(s)
10x8 ft open top container
12x8 ft open top container

issued to
TNR Offshore Celik Yapi San. ve Tic. A.S.
Ankara, Türkiye

is found to comply with
DNV standard DNV-ST-E271 – 2.7-1 Offshore containers, March 2023 (Amended December 2024)
ISO 10855-1:2024 Offshore containers and associated liftings sets – Part 1: Design, manufacture and marking of offshore containers
IMO/MSC Circular 860

Application:

Type	Max. gross mass (kg)	Max. payload (kg)	Max. sling leg angle	Enhancement factor
10x8 ft open top container	10400	7900	45	1.483
12x8 ft open top container	10000	7150	45	1.501

Issued at **Aberdeen** on **2025-06-04**

This Certificate is valid until **2030-06-03**.

for **DNV**

DNV local unit: **Istanbul**

Approval Engineer: **Elisabeth Legg**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Product description

Type	Maximum external dimensions (LxWxH)	Tare mass*
10x8 ft open top container	2991 x 2438 x 2789 mm	2500 kg
12x8 ft open top container	3658 x 2438 x 2789 mm	2850 kg

*) Tare mass is to be confirmed by weighing. The sum of tare and payload shall never exceed the maximum gross mass stated on the front page of this certificate.

Application/Limitation

Type	Design temperature	Minimum shackle pin diameter
10x8 ft open top container	-20 °C	27.8 mm
12x8 ft open top container	-20 °C	27.4 mm

The DNV surveyor shall witness all important production and testing events and issue a certificate for each container. The certificate is only valid when the container is fitted with a DNV-ST-E271 certified lifting set.

These designs may be considered as freight containers, in accordance with International Convention for Safe Containers, 1972, CSC - 2014 edition. If they are to be used as freight containers, and transported as such, in international waters, they should be approved by an IMO entrusted approval body.

Type Approval documentation

Tests carried out

Prototype tested in accordance with DNV-ST-E271.

Marking of product

Each container to be marked in accordance with DNV / ISO requirements, including:

- Data and inspection plates
- DNV emblem for offshore containers
- NV mark to be hard stamped on the data plate
- Manufacturer's Serial Number to be welded on frame
- 12x8 ft open top container shall be marked "Empty Lift only" near each set of fork lift pockets.

Periodical assessment

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out according to DNV-SE-0284 at 2 and 3.5 year intervals. Periodical assessments will, when possible, be harmonised with other surveys and audits carried out.

This certificate is only valid if required periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in <https://approvalfinder.dnv.com>