



Certificate no.:
TAS00004ZV

TYPE APPROVAL CERTIFICATE

This is to certify:

that the portable offshore unit

with type designation(s)
skid for water tank

issued to

Gulf Eagle Contracting Co. LLC
Abu Dhabi, United Arab Emirates

is found to comply with

DNV standard DNV-ST-E273 – 2.7-3 Portable offshore units, April 2016 (Amended May 2022)

Application:

Max. gross mass (kg) **6000**

Max. payload (kg) **0**

Max. sling leg angle **8**

Issued at **Aberdeen** on **2025-09-09**

This Certificate is valid until **2030-09-08**.

for **DNV**

DNV local unit: **Abu Dhabi**

Approval Engineer: **Elisabeth Legg**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Product description

Type	Dimensions (LxWxH)	Type	Operational Class	Tare mass*
Skid for water tank	7350 x 3060 x 2105 mm	B	R00	6000 kg

*) Tare mass is to be confirmed by weighing. The sum of tare and payload shall never exceed the maximum gross mass stated on the front page of this certificate.

Application/Limitation

Type	Design temperature	Test loads
Skid for water tank	0 °C	All point lift: 10.13 tonnes 2-point lift: n/a Impact test: n/a

The DNV surveyor shall witness all important production and testing events and issue a certificate on Form no. MOP 201 "Certificate for Portable Offshore Unit" for each unit.

The lifting operation and lifting equipment have not formed part of this approval.

The tank shall be transported empty of fluids during all lifting and transportation activities.

This unit should, as far as practical, be transported and lifted in relative isolation from other cargo. Any lifting shall be planned appropriately and well controlled, such that structural parts and payload will not snag on adjacent equipment or associated lifting gear. Due care shall be taken during any lifting operations to ensure that the lifting equipment does not tangle in or snag on any parts of the frame and payload, nor become detached from the lifting trunnions.

Type Approval documentation

Tests carried out

Prototype tested in accordance with DNV-ST-E273.

Marking of product

Marking shall be carried out in accordance with to DNV-ST-E273 section 6.

This design is approved with a design temperature of 0°C and shall be certified for use in a temperate climate only. It is recommended that each unit is clearly marked with words to the effect of "Only to be used in temperate climates".



Job ID: **262.1-044528-1**
Certificate no.: **TAS00004ZV**

Periodical assessment

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out according to DNV-SE-0284 at 2 and 3.5 year intervals. Periodical assessments will, when possible, be harmonised with other surveys and audits carried out.

This certificate is only valid if required periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in <https://approvalfinder.dnv.com>